



Batch/Reject Spray Marker

For large products or for machines lacking the space for an ejection system, a spray rejection system is another option for verifying rejected products.

Leary offers a Batch/Reject Spray Marker for identifying each bad product by activating the spray valve so that the defective product can be sprayed, identified and manually removed at the end of the machine. The atomizing spray valve marks the product at a specific location, and can equally be used for identifying batch quantities. The manual-adjust air intake port increases or decreases the amount of moisture and pressure of the spray mist.

The pressure tank is available in two sizes and can be filled with water and colored dye or tinted with UV. If tinted, the sprayed mark will only be visible under a UV lamp.

- · Atomized spray head
- Accurately marks product
- 5 ms response time
- Compact design
- Valve dimensions:
 107 mm (4.25 in) x 74 mm (2.9 in)
 x 25 mm (1.0 in)
- Dual valve option for doing batch and reject marks
- · Low level alarm option

www.whleary.com

PRODUCT REJECTION

Batch/Reject Spray Marker

11 Liter (3 gal) Tank



19 Liter (5 gal) Tank



Spray Valve Station



PHYSICAL CHARACTERISTICS

11 Liter (3 gal)

Dimensions

239 mm (9.40 in) w 596 mm (23.5 in) h

Weight

8.4 kg (18.5 lbs)

19 Liter (5 gal)

Dimensions

239 mm (9.4 in) w 710 mm (28 in) h

· Weight

10.2 kg (22.5 lbs)

Spray Valve Station

• Dimensions

74 mm (2.9 in) l 25 mm (1.0 in) w 409 mm (16.1 in) h

Weight

1.3 kg (2.8 lbs)

Speed

910 m/min (3000 ft/min)

 Operating Voltage 24 VDC

COMPLETE STATION INCLUDES

- One Jet 250 spray valve
- · Hose, cables and mounting
- Spray tank, 11 L (3 gal) tank

ADDITIONAL OPTIONS

- Additional spray valve
- Upgrade to 19 L (5 gal) tank
- Low level alarm
- Encoder and license for use as a rejection device

SAFETY

· CE tested

Corporate Office 8440 B West 183 Place Tinley Park, IL 60487 USA

PH: +1(708) 444-4900 sales.us@whleary.com www.whleary.com

European Office 2 Seax Way, Basildon Essex SS15 6SW United Kingdom tel: +44 (0) 1268 490035 info@whleary.co.uk www.whleary.co.uk

